

Structural Coatings

Two (2)-Coat Zinc-Rich Rapid Deployment Coating Systems for Structural Steel

List # 9.20.70

Page 1 of 1

Date: 01-Aug-2018

CUSTODIAL OFFICE : Bridge Office - (905) 704-2406

Notes:
DFT - Dry Film Thickness.

Company	Product System	Coat #	Coating Identity	Coating Colour	Thinner	Minimum DFT (µm)
International Paint (a division of Akzo Nobel Coatings Ltd) 463 Heddle Crescent Newmarket ON L3X 3J4 Canada Tel: 416-525-6009 Email: chris.grant@akzonobel.com Web: www.international-pc.com	Epoxy-Zinc / Polyaspartic Urethane	1st	Cathacoat 315	Green	T-10	90
	Epoxy-Zinc / Polyaspartic Urethane	2nd	Devthane 349 QC	U.S. Fed. Std. 16307 Grey, 10045 Brown	T-5	150
PPG Canada Inc. 8200 Keele Street Concord ON L4K 2A5 Canada Tel: 905-738-7310 Fax: 905-669-3486 Cellular: 416-347-9533 Email: dennis.oreilly@ppg.com Web: www.ppgpmc.com	Epoxy-Zinc / Polysiloxane	1st	Amercoat 68HS	Grey, Reddish	Amercoat 65	90
	Epoxy-Zinc / Polysiloxane	2nd	Amercoat PSX 700	U.S. Fed. Std. 16307 Grey, 10045 Brown	Amercoat 911 or 101	150
Sherwin-Williams Company 418 North Service Rd. E, Suite 1A Oakville ON L6H 5R2 Canada Tel: 905-849-2921 Fax: 905-849-2926 Cellular: 416-676-2954 Email: mharman@sherwin.com Web: www.sherwin.com	Epoxy-Zinc / Polyaspartic Urethane	1st	Zinc Clad III HS	Grey-Green	<27°C R6K10 or MEK; >27°C R7K104	90
	Epoxy-Zinc / Polyaspartic Urethane	2nd	Envirolastic 980 PA	U.S. Fed. Std. 16307 Grey, 10045 Brown	<27°C R7K111 or MEK; >27°C R7K216	150