

Pavements

Concrete

Joint Sealant, Rubberized Asphalt, Hot Poured

List # 3.20.45

Page 1 of 1

Date: 01-Jun-2021

CUSTODIAL OFFICE : EMO - Concrete - (416) 235-3705

NOTES:

- Pour Temperature is in degrees Celsius.

- For all products shown, method of application is either by pressure or gravity feed.

- For the purpose of this DSM, "Southern Ontario" is defined as Central Region and Districts 31, 32, 33, 41, and southern part of District 43 (the southern part is south of a line drawn from the northwest corner of District 41 to Kinmount - formerly Districts 1 to 8).

Company	Product Identity	Pour Temperature (°C)	Area of Use	Categoric Use Description
Crafco Inc. 6165 W. Detroit St. Chandler AZ 85226 2601 Tel: 602-276-0406 Fax: 480-961-0513 Toll Free: 800-528-8242 Email: sales@crafco.com Web: www.crafco.com Ontario Source: Crafco, Inc. (ON) 66 Akron Rd Toronto (Etobicoke) ON M8W 1T2 Canada Tel: 800-528-8242 Email: sales@crafco.com Web: www.crafco.com	ULTRASEAL 1190	190 - 205	Southern Ontario	For use only when joint with reservoir cut is specified. Not for use when full depth joint filling without reservoir cut is specified.
	ULTRASEAL 3405	180 - 200	All Districts	For use only when joint with reservoir cut is specified. Not for use when full depth joint filling without reservoir cut is specified.
	ULTRASEAL 3407 LM Low Modulus	175 - 190	All Districts	For use when joint with reservoir cut is specified or when full depth joint filling without reservoir cut is specified.
	Roadsaver 211 - Code #3421	190 - 210	Southern Ontario	For use only when joint with reservoir cut is specified. Not for use when full depth joint filling without reservoir cut is specified.
McAsphalt Industries Ltd. 8800 Sheppard Avenue East Toronto ON M1B 5R4 Tel: 416-281-8181 Fax: 416-281-8842 Toll Free: 800-268-4238 Email: info@mcasphalt.com Web: www.mcasphalt.com	MACSEAL 6690-4 MOD (previously BERAM 3060LM)	170 - 200	All Districts	For use when joint with reservoir cut is specified or when full depth joint filling without reservoir cut is specified.
	MACSEAL 6690-1 (previously Beram 190)	180 - 200	Southern Ontario	For use only when joint with reservoir cut is specified. Not for use when full depth joint filling without reservoir cut is specified.
	MACSEAL BDM (previously BEMALASTIC 1213 BDM)	180 - 195	Southern Ontario	For use only when joint with reservoir cut is specified. Not for use when full depth joint filling without reservoir cut is specified.